

FLARE

UP TO 90 lm/w


Transform Walls into Wonders



IP54



IK07



Tiltable Head



CLASS I



Wall Mounted Luminaire

Combining modern elegance with powerful performance, this luminaire offers exceptional brightness, outstanding efficiency, and reliable operation you can count on.



• APPLICATION



Business Campuses



Recreational Areas



Mall/retail Areas



Building Exteriors



Educational Facilities



Perimeter Areas

• CHARACTERISTICS & SPECIFICATIONS TABLE

• Technical Parameters

Input Voltage:	100-240VAC 50/60Hz
Power Factor:	>0.95
THD:	<15
Surge protection options (kV):	1KV (L-N), 2KV (L/N-PE)
Working Temp (ta):	-20°C~+55°C
Protection Class :	Class I
Color Temperature :	2700K > 3000K > 4000K > 5000K > 5700K > 6500K

• Features

Housing :	Die-Cast Aluminum
Mounting:	Wall Mounted
Optics:	Glass / PMMA
Body Finish:	Electrostatic Polyester Powder-Coated
Body Color:	Available Colors: Dark Gray, Other colors are optional
Lifetime :	L70B50 > 50,000h L80B20 > 30,000h
LED Type:	SMD
Dimming:	Optional
Switching Cycles:	>25,000

• Performance


Model	Power	Efficiency	System Lumen	Beam Angle	CRI	Source
NLC-FR	8W	90LM/W	720LM	28°	Standard: >80 Optional: >90	CREE 

*Above values are calculated based on the product with CCT 3000K


*Values shown are subject to $\pm 10\%$ tolerance

• Drawing

W231 x D77 x H48mm



• LIGHT DISTRIBUTIONS CURVE



• Certificates

